



# Premium ATF6 Automatic Transmission Fluid

Revision n°02

Revision date: 2025-07

## Description

AISIN Premium ATF 6 is a synthetic Long Life Multi ATF. The product has been specially developed for use in modern automatic transmissions in cars and vans. New generation additives and advanced, synthetic base oils provide the following properties:

- Excellent oxidation stability: extending the service life of the fluid
- Outstanding lubrication properties, even under the most extreme conditions
- Very high resistance to wear, corrosion and foaming
- Excellent shear stability
- An extremely low pour point: can be used at extremely low temperatures
- A very high viscosity index: reliable operation of the transmission at both high and low temperatures

## Applications

AISIN Premium ATF 6 is a synthetic, multi-functional Long Life ATF for modern, electronically-controlled automatic transmissions in cars and vans. This product is also suitable for use in power steering systems.

## Specifications

Performance level:

- Aisin Warner JWS 3309 / JWS 3317
- Allison C4 / TES-389 / TES-295 / TES-668 BMW ATF 6 (83 22 2 355 599)
- BMW 7045E / 8072B / LA2634 / LT71141
- Chrysler / Dodge / Jeep MS 9602, ATF +4, ATF +3 Fiat 9.55550-AV4
- Ford Mercon V, WSS-M2C922-A1, WSS-M2C924-A
- GM Dexron IID, Dexron IIE, Dexron IIIG, Dexron IIH GM Dexron II/IID/IIE/IIIG/IIH / TASA
- Honda ATF-Z1 (except in CVT)
- Hyundai/Kia SP-II/SP-III/RED-1K, Isuzu ATF II/III
- Jaguar JLM 20238/20292/21044, JASO M315 Type 1A Mazda M-III/Type T-IV / JWS 3309
- Mercedes MB 236.14, MB 236.12
- Mercedes MB 236.91, MB 236.11, MB 236.10 Mitsubishi SP-II, SP-III, ATF-J2
- Nissan Matic-D, Matic-J, Matic-K
- Subaru ATF HP, Suzuki ATF 3314/3317 Toyota / Lexus T, T-II, T-III, T-IV
- VW G 052 025 / 052 055
- Volvo 1161540
- VW G 052 162 / 052 990 / 055 025 ZF TE-ML 11A / 11B
- ZF ATF 1375.4 (6HP Transmissions)

## **Typical Properties**

|                   |                    | ATF6  |
|-------------------|--------------------|-------|
| Density@15°C      | kg/l               | 0,861 |
| Viscosity 40 °C   | mm <sup>2</sup> /s | 35,80 |
| Viscosity 100 °C  | mm <sup>2</sup> /s | 7,40  |
| Viscosity Index   |                    | 180   |
| Flash Point(COC)  | °C                 | 190   |
| Pour Point        | °C                 | -57   |
| Total Base Number | mgKOH/g            | 4,0   |
| Brookfield -40°C  | mPa · s            | 13000 |